

- Bio-based
- High Performance Liquid Anti-Icer
- USDA Bio-Preferred
- Magnesium Chloride Free

Description and Application:

FUSION®30-70 BLEND is a ready to use product that does not require mixing. Prewetting reduces bounce and scatter of your salt, keeping more product on the road and getting your salt into solution faster. The suggested rates should be considered as starting points and should be adjusted as needed based on weather conditions and road surface temperatures.

Anti-icing:

- Apply at 20 to 30 gallons per lane mile.
- Apply using a stream application.
- Begin application when pavement temperatures are expected to be at or below 32°F.

Benefits:

- Prevents ice and snow from bonding to the pavement, making removal easier.
- Lowers maintenance costs by reducing applications/quantities needed.
- No dust-causing abrasives needed.

Prewetting:

- Apply at 5 to 10 gallons per ton at the spinner or directly to the salt/sand during loading.

Benefits:

- Enhances the deicing performance of dry salt/sand by keeping it on the road.
- Starts the deicing process immediately.
- Reduces bounce and scatter loss during application.
- Less salt/sand is required for the same results.

TECHNICAL INFORMATION:	
Principal Application(s)	Anti-Icing
	Pre-Wetting
Color	Dark Amber
Specific Gravity	1.225
pH	8 - 9
Solids	33%

** Product specifications are subject to change slightly with raw material variances



SINCE 2012 OSSIAN HAS PROVIDED
MOBILE ACCESS TO OUR PRODUCTS'
SAFETY DATA SHEETS THROUGH
QR CODES ON ALL PACKAGES.

www.ossian.com

Ossian Inc. Davenport, Iowa Phone: 563-324-3381 800-553-8011 Fax: 563-324-0751 icemelt@ossian.com